



# 3285

MICRO-GROOVED POLYSTYRENE SANDWICH DOOR

08 36 13/CHI  
BUYLINE 3132

www.chiohd.com

C.H.I. OVERHEAD DOORS



9' x 7' 3285 white with optional white aluminum full-view window section

DURABLE. RELIABLE.

## SPECIFICATIONS, OPTIONAL FEATURES AND ACCESSORIES



### EXHAUST PORT

An exhaust port is an optional feature to keep those unwanted fumes from lingering around the work area.



### INSIDE SIDE LOCK

The inside side lock is a wise decision for added security when you are not around. (Torsion only)

### OPTIONAL WINDOW DESIGNS

24" SECTION HEIGHT




24" x 6"



24" x 12"



34" x 16"



Full-View

COLOR SELECTION

WHITE

ALMOND

SANDSTONE

BROWN

Note: Refer to samples at your local C.H.I. Distributor for exact color match.

## 26-GAUGE MODEL 3285, Insulated

### SECTIONS

- Features four evenly spaced micro-grooves that run horizontally across each section
- Double-sided steel doors are 26-gauge front and 27-gauge back for sturdiness
- Concealed steel back-up plates run from top to bottom of each section for secure hardware attachment
- Section joints are tongue-and-groove
- White painted end stiles
- Bottom "U" type astragal is a standard feature
- Available in white, almond, sandstone or brown

### TRACKS

- Tracks are 2" or 3", as specified
- Available in bracket mount, angle mount, clip angle mount, 12" radius, 15" radius, high lift, vertical lift, roof pitch, or dual track low headroom

### HARDWARE

- Package includes 11-gauge or 14-gauge hinges, as specified
- 2" or 3" long-stem or short-stem steel ball bearings rollers
- Heavy-duty adjustable top roller brackets

### SPRINGS

- Torsion springs are helically wound with stress relieved, oil-tempered wire
- Springs are individually-calibrated for each door
- Counter-balance torsion shafts are galvanized for rust resistance
- High cycle spring options may be specified

### INSULATION TYPE

- CFC free polystyrene core is secured in place with a urethane adhesive to increase structural integrity
- R-value - 10.29

FEATURES


VISIT YOUR DOOR PROFESSIONAL AT:

C.H.I. Overhead Doors are manufactured in Arthur, Illinois, USA.



Wind can be unpredictable and destructive. This is why C.H.I. Windbreaker Series and iSeries doors are designed, tested, and built to the most rugged specifications. Wind chamber tested to ensure wind-load resistance, these extra-sturdy designs provide enhanced defense against the elements.

C.H.I. Overhead Doors developed the resilient Windbreaker Series garage doors to protect against high wind conditions. The super-resilient C.H.I. iSeries Impact Approved doors have strength designed to withstand direct collision of projectiles and other windborne debris at high speeds.



### DOOR CONSTRUCTION

CFC free polystyrene insulation is secured in place with a urethane adhesive to increase structural integrity. The front and back skins are locked together in a tongue and groove design for years of worry free protection.

R-value - 10.29

All information presented is based on the specifications and features available at the time of printing and is subject to change without notice.